

... simple but perfect

SideCar basic and SideCar basic plus

Coin-in and coin-out module

SideCar basic and SideCar basic plus are solutions to extend self-service devices as ATM, Cash Recycler or Cash Dispenser under XFS with additional Coin Deposit and optionally even with coin dispensing functionality. The Coin Deposit solution is available with different coin bin solutions. Optionally the devices can be equipped with a very quick Coin Dispenser for up to 4 denominations (SideCar basic) or even with up to 8 denominations (SideCar basic plus). Housing may be mechanically adapted to the host device. Innovative materials in industrial quality for coin-disk and coin-path ensure high counting speed but a low noise level.







Combination with TCR



Low noise coin disk with cleaning-holes





Blockage-checker



Easy to access



Dispensing hoppers



Counter







Operated

Flexible use

- · Coin tray unit (optionally lockable)
- · Pre-cleaning due to intelligent dirt-separators
- Blockage-checker separates and rejects foreign objects automatically
- Keyboard-panel for supervisor-operation (optional)
- Parallel dispense of coin hoppers
- Dispensing speed up to 40 coins / sec.

Easy integration with varying functions

- · XFS protocol for communication with ATM, TCD or TCD
- · Multi-coin-bin solution for 2 or 4 bins (optional)
- · Electronic journal for download of statistical data and technical information
- All modules highly accessible
- · Separated coin compartment made of 3mm steel sheet
- · Illuminated output tray for rejected coins

Modular coin-detection system in its 4th generation

- · Magnetic sensor for coin alloy
- · Capacitive sensor of coin-mass
- · Matrix-sensor of coin-profile
- CCD diameter sensor with 256px resolution (optional)

Counting speed		Up to 1.200 coins/minute	Capacity coin hopper		1.200 coins
Dispensing speed		Up to 40 coins/sec.	Capacity dispensing hopper		Up to 3.500 coins
WxDxH	basic	320 x 1.050 x 1.634 mm	Weight	basic	145 kg
	basic plus	430 x 880 x 1.631 mm		basic plus	165 kg
Power supply		100-240 V, 50-60 Hz	Colour		RAL 7035/7021
OPTIONS					
Configurable access control for 24h use			XFS Integration		
Multi-coin-bin solution with			Diameter sensor (CCD)		
preselection for 1, 2 or 4 coin-bins			SideCar bas	sic: Coin dis	spensing to 4 denom.
(SideCar basic 15 kg/bin; SideCar basic plus 20 kg/bin)			SideCar bas	sic Coin dis	spensing up to 8 denon